






Dial Combo Lock Directions - 4 Wheel Fixed

	<p>Turn the dial to the RIGHT more than 4 times:</p> <p>Pass through the first combo number 3 times, then set the combo number at the opening index.</p>	
	<p>Turn the dial to the LEFT 3 times:</p> <p>Pass through the second combo number twice, then set the 2nd combo number at the opening index.</p>	
	<p>Turn the dial to the RIGHT 2 times:</p> <p>Pass through the third combo number once, then set the third combo number at the opening index.</p>	
	<p>Turn the dial to the LEFT and set the last combo number at the opening index.</p>	
	<p>You should now be able to turn the key and open the safe. Please memorise or keep your combination in a safe place, away from your safe. Always test your combination with the door open.</p>	

Opening Index



Bolt Down Instructions.

1. Remove the bolt cap (unscrew anti-clockwise) May require a light tap with a hammer to loosen.
 2. Locate the unit into the chosen position and open the door.
 3. Mark the position of the hole (through the hole)
 4. Slide the unit away from the mark and drill a 5/8" hole in the concrete floor with a masonry drill to a minimum depth of 65mm.
 5. After removing the dust from the hole, gently hammer the Loxin (supplied) into the hole until it is flush with the floor
 6. Re-locate the unit into position and insert the bolt (supplied) through the hole and tighten until firm.
- Although we recommend and supply a Loxin and bolt for installation. The installer may choose another method on installation based on the location. Any warranty and guarantee will be lost if additional holes are made in the cabinet.